

BUS O2YS(St)CY 1x2x0,64/2,6 mm**PROFIBUS DP SYMMETRICAL CABLE**Operating voltage
max 100 VTest voltage
700 VTemp. range
fixed installation
from - 30°C to + 70°CBending radius
10xDFlame retardant
PN-EN 60332-1-2Indoor
applicationElectromagnetic
compatibility**APPLICATIONS**

BUS O2YS(St)CY 1x2x0,64/2,6 mm is cable intended for industrial PROFIBUS DP control systems.

For proper transmission of digital and analogue signals the cable is protected by a specially designed and highly effective collective shield against external electromagnetic interferences.

Cable outer sheath is oil-resistant.

The cables are suitable for fixed indoor installations.

CONSTRUCTION

- bare annealed copper single wire conductors of diameter 0.64 mm (22 AWG),
- foam-skin polyethylene insulation - identification colour code: red and green,
- insulated conductors twisted into a pair,
- collective shield incorporating an aluminium-polyester tape under a tinned copper wire braid,
- violet PVC cable sheath.

AVAILABLE UPON REQUEST

BUS O2YS(St)CYv 1x2x0,64/2,6 mm - cable of enhanced and oil resistant PVC sheath, suitable for outdoor installations and direct earth burial.

BUS O2YS(St)CY2Y 1x2x0,64/2,6 mm - cable with additional polyethylene (PE) sheath, suitable for outdoor installations and direct earth burial.

CHARACTERISTICS

Characteristic impedance	150 ± 15 Ω	Transfer impedance at 30 MHz, maximum	50 mΩ/m
Mutual capacitance at 1 kHz, approximate	30 nF/km	DC loop resistance at 20°C, maximum	110 Ω/km
Insulation resistance, minimum	5 GΩ·km	DC shield resistance at 20°C, maximum	9.7 Ω/km
Operating voltage	100 V	Voltage test	700 V rms
Attenuation loss, maximum at 38.4 MHz	4 dB/km	Operating temperature range	from - 30 to + 70 °C
Attenuation loss, [dB/100m] max - at frequency [MHz]:		Minimum bending radius	10 x cable diameter
1	1.2	Cable combustibility	flame retardant
4	2.2	Combustibility tests	PN-EN 60332-1-2, IEC 60332-1-2
10	3.2	Reference standards	DIN 19245 T3, EN 50170
16	4.2		

CE = the cable meets requirements of the low voltage directive 2014/35/EU

Product No.	Cable type	Number of conductors x conductor cross-section	Cable outer diameter (appr.)	Copper index	Cable weight (appr.)
		mm	mm	kg/km	kg/km
0182 001	O2YS(St)CY	1x2x0,64/2,6	8.0	20.5	67
0182 003	O2YS(St)CYv	1x2x0,64/2,6	10.0	20.9	108

TECHNOKABEL S.A. reserves the right to change specifications without prior notice.