


FTP kat.5e 4x2x0,5 mm - 155 MHz

page 1 of 2

LOCAL AREA NETWORK CABLES**APPLICATIONS**

FTP kat.5e 4x2x0,5 mm cables are intended for multimedia computer networks (data, sound and HDTV transmission), including structural wiring of buildings, applied in industrial and other dedicated networks sensitive to electromagnetic interferences.

The overall shield protects the cables against external electromagnetic interferences and prevents emission of interferences produced in the cables.

The cables are also applied in computer networks of increased binary transfer where simultaneous transmission in both directions in all 4 symmetrical circuits is used (full duplex, Gigabit Ethernet technique).

The cables are suitable for fixed indoor installations.

CONSTRUCTION

- annealed copper single wire conductors of diameter 0.51 mm, 24 AWG,
- polyethylene (PE) insulation coloured: white-blue and blue, white-orange and orange, white-green and green, white-brown and brown,
- insulated conductors twisted into pairs,
- pairs laid-up into a cable core,
- collective shield, incorporating an aluminium-polyester tape and an annealed tinned copper single drain wire of diameter 0.5 mm,
- PVC cable sheath, grey RAL 7035, other colours also available.

AVAILABLE UPON REQUEST

FTP-H kat.5e 4x2x0,5 mm - halogen free material sheathed cables applied in locations where, in case of fire, higher safety level is required. The cables are flame retardant and their smoke emission is low, emitted fumes are non toxic and non corrosive.

FTP kat.5e 4x2x0,5 mm - 155 MHz

page 2 of 2

CHARACTERISTICS

Characteristic impedance	100 ± 15 Ω	Minimum shielding attenuation at the frequency f=30 ÷ 1000 MHz	50 dB
Mutual capacitance of any pair at 1 kHz, approximate	50 nF/km	Shielding impedance at 10 MHz, maximum	100 mΩ/m
Capacitance unbalance of any pair to ground at 1 kHz, max.	1600 pF/km	DC loop resistance at 20°C, maximum	188 Ω/km
Insulation resistance, minimum	5000 MΩ·km	Resistance unbalance of any pair of conductors, max.	2 %
Operating voltage	150 V	Phase delay dispersion of symmetrical circuits	45 ns/100 m
Voltage test	700 V rms	Phase delay T	534+36/√f ns/100 m
Velocity of propagation	65 %	Operating temperature range during operation	from - 20 to + 70°C
Return loss, minimum at f=4÷10 MHz	20+5lg(f) dB	during installation	from 0 to + 50°C
Return loss, minimum at f=10÷20 MHz	25 dB	Minimum bending radius	4 x cable diameter
Return loss, minimum at f=20÷155 MHz	25-8.6lg(f/20)dB	Cable combustibility	flame retardant
		Combustibility tests	PN-EN 60332-1-2, IEC 60332-1-2
		Reference standards	PN-EN 50288-2-1, IEC 61156-5 ISO/IEC 11801, TIA/EIA 568 A

Attenuation loss, maximum

f	[MHz]	1	4	8	10	16	20	25	31.25	62.5	100	155
a	[dB/100 m]	2.1	4.3	5.9	6.6	8.2	9.2	10.5	11.8	17.1	22	28.1

Near end cross-talk between pairs, minimum

f	[MHz]	1	4	8	10	16	20	25	31.25	62.5	100	155
NEXT	[dB]	65.3	56.3	51.8	50.3	47.3	45.8	44.3	42.9	38.4	35.3	32.5
PSNEXT	[dB]	62.3	53.3	48.8	47.3	44.3	42.8	41.3	39.9	35.4	32.3	29.5
ACR	[dB]	68.3	57.2	51.0	48.8	44.0	41.5	38.9	36.2	26.4	18.3	4.4

Far end cross-talk between pairs, minimum

f	[MHz]	1	4	8	10	16	20	25	31.25	62.5	100	155
ELFEXT	[dB]	63.8	51.7	45.7	43.8	39.7	37.7	35.8	33.9	27.8	23.8	19.9
PSELFEXT	[dB]	60.8	48.7	42.7	40.8	36.7	34.7	32.8	30.9	24.8	20.8	16.9

CE = the cable meets requirements of the low voltage directive 2014/35/EU

Product No.	Number of pairs (x 2) x conductor diameter	Cable outer diameter (appr.)	Copper index	Cable weight (appr.)
	mm	mm	kg/km	kg/km
0013 005	4 x 2 x 0,5	5.8	17.5	36.0

TECHNOKABEL S.A. reserves the right to change specifications without prior notice.