

INSTYTUT KOLEJNICTWA OŚRODEK JAKOŚCI I CERTYFIKACJI ul. J. Chłopickiego 50, 04-275 Warszawa

tel.: +48 22 47-31-392, tel/fax.: +48 22 612-31-32



AC 128

CERTIFICATE OF CONFORMITY IK CZ - 050/2019

Name and address of certificate holder:	Technokabel Spółka Akcyjna ul. Nasielska 55; 04-343 Warszawa		
Name and address of the manufacturer:	Technokabel Spółka Akcyjna ul. Wiatraczna 28; 06-550 Szreńsk k/Mławy		
Name of the product:	Halogen-free cables for rail vehicles		
Type/variety	Cable name	Standard related to cable geometry	Diameter Ø, mm
·) - · · · · · · · · · · · · · · · · ·	TECHRAY-303 3,6/6 kV 2,5mm ² +240mm ²	PN-EN 50264-3-1:2008	9,4 +32,0

The product meets the requirements of:

PN-EN 45545-2+A1:2015-12 Railway applications – Fire protection on railway vehicles – Part 2: Requirements for materials and elements in the scope of fire properties according to: R15 and R16 at the Hazard Level HL1, HL2 and HL3 for vehicles according to design category: N (standard vehicles), A (vehicles forming part of an automatic train having no emergency trained staff on board), D (double decked vehicles) and S (sleeping and couchette vehicles), which are in operation category no.: 1 - vehicles for operation in infrastructure in which they can be stopped with a minimum delay and can immediately reach a safe area, 2 - vehicles for operation on underground sections in tunnels and / or on structures raised above the terrain, with the possibility of side evacuation and in which there are rescue stations or stations that provide a safe place for passengers, accessible after a long driving time, 4 - vehicles for operation on underground sections, in tunnels and / or on structures raised above the terrain, without the possibility of side evacuation and in which there are rescue stations or stations, which provide a safe place for passengers, accessible after a long driving time, 4 - vehicles for operation on underground sections, in tunnels and / or on structures raised above the terrain, without the possibility of side evacuation and in which there are rescue stations or stations that provide a safe place for passengers, accessible after a long driving time, 4 - vehicles for operation on underground sections, in tunnels and / or on structures raised above the surface of the terrain, without the possibility of side evacuation and in which there are rescue stations or stations that provide safe passenger seat, accessible after a short driving time.

In accordance with the report of tests and evaluation report conducted by:

Materials and Structure Laboratory – Railway Institute Warsaw, Poland Lapi Laboratorio Prevenzione Incendi S.p.A., Italy

Test report, evaluation report:

Test report No. IK.LKA105.A216/19 of 18.11.2019, Test report No. IK.LKA105.A217/19 of 18.11.2019, Rapporto Di Prova No. 1996.1Cl0110/19, Rapporto Di Prova No. 1997.1Cl0110/19 Rapporto Di Prova No. 2074.1Cl0110/19, Rapporto Di Prova No. 2075.1Cl0110/19

Scope of utility:

The product is intended for rolling stock.

The right to use the Certificate of Conformity from **29.11.2019 to 28.11.2022** is valid exclusively for the copies of products of the same parameters as specimen (specimens) subjected to scrutiny and complying with mentioned standard.

Certification according to Certification Program PCW-02

KIEROWNIK JAKOŚCI I CERTYFIKACJI

The Head of Quality and Certification Centre



ZASTEPCA DYREKTC OLE DS. INTEROPERACYJNOŚC arek Pa

Director of Railway Institute